

R-Code	Street setback and front fences		Lot boundary setback		Open space		Garage setback and width and vehicular access		Parking		Overshadowing		Privacy	
	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision
RMD – R60	2m	<p>2m minimum, no average</p> <p>1m to porch /veranda, no maximum length</p> <p>1m minimum to secondary street</p> <p>Front fences within the primary street setback area being a maximum height of 900mm above natural ground level, measured from the primary street side of the front fence</p>	<p><u>Boundary setbacks</u> 1 to 1.5m for wall height 3.5m and less (subject to wall length and major openings)</p> <p><u>Boundary walls</u> 2/3 length one side boundary, max 3.5m high and 3m average height</p>	<p><u>Boundary setbacks</u> 1.2m for wall height 3.5m or less with major openings</p> <p>1m for wall height 3.5m or less without major openings</p> <p><u>Boundary walls</u> No maximum length to both side boundaries</p>	<p>40% open space (60% site cover)</p> <p>16m² courtyard</p> <p>1/3 required outdoor living area (OLA) may be covered</p> <p>Minimum dimension 4m</p>	<p>An outdoor living area (OLA) with an area of 10% of the lot size or 20m², whichever is greater, directly accessible from a habitable room of the dwelling and located behind the street setback area</p> <p>At least 70% of the OLA must be uncovered and includes areas under eaves which adjoin uncovered areas</p> <p>The OLA has a minimum 3m length or width dimension</p> <p>No other R-Codes site cover standards apply</p>	<p><u>Rear load</u> Nil – provided laneway is minimum of 6m wide</p> <p><u>Front load</u> 4.5m or 0.5m behind dwelling alignment subject to averaging requirements</p> <p>Garage width limited to maximum 50% of lot frontage where garage in front of or within 1m of building</p>	<p><u>Rear load</u> 0.5m garage setback to laneway</p> <p><u>Front load</u> 4.5m garage setback from the primary street and 1.5m from a secondary street</p> <p>The garage setback from the primary street may be reduced to 4m where an existing or planned footpath or shared path is located more than 0.5m from the street boundary</p> <p>For front loaded lots with street frontages between 10.5 and 12m, a double garage is permitted to a maximum width of 6m as viewed from the street subject to:</p> <ul style="list-style-type: none"> garage setback a minimum of 0.5m behind the building alignment; a major opening to a habitable room directly facing the primary street; an entry feature consisting of a porch or veranda with a minimum depth of 1.2m; and, no vehicular crossover wider than 4.5m where it meets the street <p>Lots with a frontage less than 10.5m or not compliant with the above require single or tandem garaging</p>	Two on-site bays	One on-site bay where dwelling has two bedrooms or less	50% of the adjoining site area	No maximum overshadowing	3m to bedrooms and studies	No privacy provisions apply

R-Code	Street setback and front fences		Lot boundary setback		Open space		Garage setback and width and vehicular access		Parking		Overshadowing		Privacy	
	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision
RMD – R40	4m	<p>2m minimum, no average</p> <p>1.5m to porch/veranda, no maximum length</p> <p>1m minimum to secondary street</p> <p>Front fences within the primary street setback area being a maximum height of 900mm above natural ground level, measured from the primary street side of the front fence</p>	<p><u>Boundary setbacks</u> 1 to 1.5m for wall height 3.5m and less (subject to wall length and major openings)</p> <p><u>Boundary walls</u> 2/3 length one side boundary, max 3.5m high and 3m average height</p>	<p><u>Boundary setbacks</u> 1.2m for wall height 3.5m or less with major openings</p> <p>1m for wall height 3.5m or less without major openings</p> <p><u>Boundary walls</u> To both side boundaries subject to: No maximum length to one side boundary, 2/3 max length to second side boundary for wall height 3.5m or less</p>	<p>45% open space (55% site cover)</p> <p>20m² courtyard</p> <p>1/3 required OLA area may be covered</p> <p>Minimum dimension 4m</p>	<p>An outdoor living area (OLA) with an area of 10% of the lot size or 20m², whichever is greater, directly accessible from a habitable room of the dwelling and located behind the street setback area</p> <p>At least 70% of the OLA must be uncovered and includes areas under eaves which adjoin uncovered areas</p> <p>The OLA has a minimum 3m length or width dimension</p> <p>No other R-Codes site cover standards apply</p>	<p><u>Rear load</u> Nil – provided laneway is minimum 6m wide</p> <p><u>Front load</u> 4.5m or 0.5m behind dwelling alignment subject to averaging requirements</p>	<p><u>Rear load</u> 0.5m garage setback to laneway</p> <p><u>Front load</u> 4.5m garage setback from the primary street and 1.5m from a secondary street</p> <p>The garage setback from the primary street may be reduced to 4m where an existing or planned footpath or shared path is located more than 0.5m from the street boundary</p> <p>For front loaded lots with street frontages between 10.5 and 12m, a double garage is permitted to a maximum width of 6m as viewed from the street subject to:</p> <ul style="list-style-type: none"> garage setback a minimum of 0.5m behind the building alignment; a major opening to a habitable room directly facing the primary street; an entry feature consisting of a porch or veranda with a minimum depth of 1.2m; and, no vehicular crossover wider than 4.5m where it meets the street <p>Lots with a frontage less than 10.5m or not compliant with the above require single or tandem garaging</p>	Two on-site bays	As per R-Codes	35% of the adjoining site area	<p>No maximum overshadowing for wall height 3.5m or less</p> <p>No maximum overshadowing for wall height greater than 3.5m where overshadowing is confined to the front half of the lot. If overshadowing intrudes into rear half of the lot, shadow cast does not exceed 35%</p>	<p>4.5m to bedrooms and studies</p> <p>6.0m to all other major openings</p> <p>7.5m to balconies or similar</p>	<p>With the exception of RMD60, R-Codes clause 5.4.1 C1.1 applies to RMD 40, 30 & 25, however the setback distance is 3m to bedrooms and studies, 4.5m to major openings to habitable rooms other than bedrooms and studies and 6m to unenclosed outdoor active habitable spaces</p>

R-Code	Street setback and front fences		Lot boundary setback		Open space		Garage setback and width and vehicular access		Parking		Overshadowing		Privacy	
	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision
RMD – 25	6m	<p>3m minimum</p> <p>1.5m to porch/veranda, no maximum length</p> <p>1.5m minimum to secondary street</p> <p>Front fences within the primary street setback area being a maximum height of 900mm above natural ground level, measured from the primary street side of the front fence</p>	<p><u>Boundary setbacks</u> Wall height 3.5m & less: 1m/1.5m (subject to wall length and major openings)</p> <p><u>Boundary walls</u> 2/3 length one side boundary, max 3.5m high and 3m average height</p>	<p><u>Boundary setbacks</u> 1.2m for wall height 3.5m or less with major openings</p> <p>1m for wall height 3.5m or less without major openings</p> <p><u>Boundary walls</u> To both side boundaries subject to: 2/3 length to one side boundary, 1/3 max length to second side boundary for wall height 3.5m or less</p>	<p>50% open space (50% site cover)</p> <p>30m² courtyard</p> <p>1/3 required OLA area may be covered</p> <p>Minimum dimension 4m</p>	<p>An outdoor living area (OLA) with an area of 10% of the lot size or 20m², whichever is greater, directly accessible from a habitable room of the dwelling and located behind the street setback area</p> <p>At least 70% of the OLA must be uncovered and includes areas under eaves which adjoin uncovered areas</p> <p>The OLA has a minimum 3m length or width dimension</p> <p>No other R-Codes site cover standards apply</p>	<p><u>Rear load</u> Nil – provided laneway is minimum 6m wide</p> <p><u>Front load</u> 4.5m or 0.5m behind dwelling alignment subject to averaging requirements</p>	<p><u>Rear load</u> 0.5m garage setback to laneway</p> <p><u>Front load</u> 4.5m garage setback from the primary street and 1.5m from a secondary street</p> <p>The garage setback from the primary street may be reduced to 4m where an existing or planned footpath or shared path is located more than 0.5m from the street boundary</p> <p>For front loaded lots with street frontages between 10.5 and 12m, a double garage is permitted to a maximum width of 6m as viewed from the street subject to:</p> <ul style="list-style-type: none"> garage setback a minimum of 0.5m behind the building alignment; a major opening to a habitable room directly facing the primary street; an entry feature consisting of a porch or veranda with a minimum depth of 1.2m; and, no vehicular crossover wider than 4.5m where it meets the street <p>Lots with a frontage less than 10.5m or not compliant with the above require single or tandem garaging</p>	Two on-site bays	As per R-Codes	25% of the adjoining site area	<p>No maximum overshadowing for wall height 3.5m or less</p> <p>No maximum overshadowing for wall height greater than 3.5m where overshadowing is confined to the front half of the lot. If overshadowing intrudes into rear half of the lot, shadow cast does not exceed 25%</p>	<p>4.5m to bedrooms and studies</p> <p>6.0m to all other major openings</p> <p>7.5m to balconies or similar</p>	<p>With the exception of RMD60, R-Codes clause 5.4.1 C1.1 applies to RMD 40, 30 & 25, however the setback distance is 3m to bedrooms and studies, 4.5m to major openings to habitable rooms other than bedrooms and studies and 6m to unenclosed outdoor active habitable spaces</p>